

VAM² SL 9.0



WHEELSIZE	29"	29"	29"	29"
SIZE / CM	S/39	M/42	L/44	XL/46

ART NO. / Black D673617130 D673617131 D673617132 D673617133

-  MAX Carbon technology frame, 125mm F.O.L.D. GEN3 kinematics, 148x12 thru axle, internal cable routing, Post Mount 180 mm
-  FOX 34 Float Factory 29, 110x15 mm, 51 mm rake
-  FOX Float Factory , 2-position lever, 210/50 mm, hardware: 25.0 x 8.0 mm, no Bushing
-  130 mm
-  Fazua Ride 60, 60 Nm, 430 W max.
-  Fazua LED Hub + Ring Control
-  Fazua 36V (430Wh)
-  SRAM AXS POD Ultimate
-  Rotor eKAPIC RF Link 29
-  SRAM X0 Eagle Transmission, 12-speed
-  SRAM XS-1295, 12-speed
-  SRAM Level Ultimate Stealth, 4-piston, SRAM Level Ultimate Stealth, 4-piston
-  180 mm / 180 mm
-  Mavic Crossmax XL R 29, carbon, 622-30, 15x110 mm / 12x148 mm
-  Schwalbe Nobby Nic 2.4 SuperGround SpeedGrip
-  Schwalbe Wicked Will 2.4, SuperGround SpeedGrip
-  FOCUS C.I.S. 2.0 MTB One Piece SL Cockpit, 800 mm, rise: 25 mm
-  VP VPG-122A
-  FOX Transfer SL Factory, 31,6mm
-  Prologo Proxim W850 Neck
-  135