

FOCUS SAM² 6.9



Wheel size	29in/27-5in	29in/27-5in	29in/27-5in	29in/27-5in
Size / cm	S/39	M/42	L/44	XL/46
Art.Nr. / Black (600 Wh)	D680511015	D680511016	D680511017	D680511018
Art.Nr. / Black (800 Wh)	D680511015	D680511016	D680511017	D680511018
Art.Nr. / White (600 Wh)	D680511010	D680511011	D680511012	D680511013
Art.Nr. / White (800 Wh)	D680511010	D680511011	D680511012	D680511013

- Fox 38 Factory, Grip X2, 170 mm
- 7005 hydroformed aluminium, 165 mm F.O.L.D. kinematics, 148x12 mm thru axle, Post Mount 180 mm
- XL | 46
- ACROS ZS56/ZS66 (ICR), FOCUS C.I.S. Integrated angle headset
- FOCUS C.I.S. 2.0, 40 mm
- Bosch Performance Line CX, 85 NM, 100 NM update via Flow App available summer
- fi'zi:k Ridon X5
- OneUp V3, S / M / L / XL: 150 / 180 / 210 / 210 mm, 34,9 mm
- DT Swiss HF 1900, alloy, front: 29", rear: 27,5"
- From: 26 Kg (600 Wh)
- Schwalbe Magic Marry, Super DH, ADDIX Ultra Soft, 27,5 x 2,4"
- SRAM GX Eagle Transmission
- Fox DHX Performance, Coil: 350/400/500/600 lbs (S/M/L/XL), 165 mm
- Bosch PowerTube Li-Ion
- OneUp Riser, width: 800 mm, rise: 35 mm
- SRAM GX Transmission, 10-52T
- Samox, 165 mm
- SRAM Eagle 90 Transmission
- Bosch Mini Remote
- ODI Elite Pro
- TRP EVO Pro, 4-piston
- 150 Kg
- SRAM Eagle 90 Transmission, 12-speed